



# STOP THE DROP - RISK CHECKER

## Working with mobile scaffolding - Does this hazard exist?

Hazard		YES	NO
1.	People falling from scaffold platforms.	<input type="radio"/>	<input type="radio"/>
2.	Materials falling from scaffold platforms.	<input type="radio"/>	<input type="radio"/>
3.	Scaffold collapsing.	<input type="radio"/>	<input type="radio"/>
4.	Plant, vehicles or persons colliding with scaffold.	<input type="radio"/>	<input type="radio"/>
5.	Other (please state)	<input type="radio"/>	<input type="radio"/>

YES IT DOES - if you have ticked at least one answer in the YES column

Please note that the list below may not cover all the possible cases in which there are hazards. Please add additional information for your own purposes

### Preventative measures being used to reduce risk

<input type="checkbox"/>	All scaffold towers will be properly constructed in accordance with British and European Standards, manufacturer's instructions and must comply with current legislation	<input type="checkbox"/>	Stabilisers, with pad feet, or outriggers will be used as appropriate.
<input type="checkbox"/>	Scaffold towers will be assembled, dismantled or significantly altered only by persons who have received appropriate and specific training and under the supervision of a competent person.	<input type="checkbox"/>	To ensure stability, the height to least base ratio will not be greater than the manufacturers recommendations.
<input type="checkbox"/>	Toe boards and guardrails will be provided where a person is at risk of falling a distance which is liable to cause personal injury, toe-boards shall be suitable and sufficient to prevent the fall of any person, material, or object, from any place of work; and any intermediate guard-rail or similar means of protection, shall be positioned to provide suitable protection.	<input type="checkbox"/>	Any surface upon which a supporting structure rests will be stable, of sufficient strength and of suitable composition to safely support the structure, the working platform, and any loading intended to be placed on to the working platform.
<input type="checkbox"/>	The dimensions, form and layout of working platforms will be appropriate to the nature of the work to be performed, and suitable for the loads to be carried, and must permit work in safety.	<input type="checkbox"/>	A safe means of access will always be provided either by way of suitable internal ladders, or ladder sections integrated with frame. Climbing, using the horizontal members will not be permitted.
<input type="checkbox"/>	Equipment will only be used outside if weather conditions permit safe use.	<input type="checkbox"/>	No scaffold tower will be used until a competent person has inspected and approved it for use. It shall be inspected at regular intervals not exceeding 7 days, after any event, which may have affected its strength or stability, or after substantial alteration etc.
<input type="checkbox"/>	Towers will only be moved after materials and users are removed from the working platforms.	<input type="checkbox"/>	Traffic/pedestrian routes will be used to prevent contact with structures.
<input type="checkbox"/>	OTHER (Please specify)	<input type="checkbox"/>	Scaffold towers will be erected on firm level ground.
<input type="checkbox"/>		<input type="checkbox"/>	OTHER (Please specify)