

E152-ZE0

Edge Server - 1U UP GPU supported



Features

- Supports 1 x double slot GPU cards
- Single AMD EPYC™ 7003 series processor family
- 8-Channel RDIMM/LRDIMM DDR4 per processor, 8 x DIMMs
- 2 x 1Gb/s LAN ports (Intel® I350-AM2)
- 1 x Dedicated management port
- 2 x 2.5" SATA/SAS/Gen4 NVMe hot-swappable HDD/SSD bays
- 2 x Ultra-Fast M.2 with PCIe Gen4 x4 interface
- 2 x PCIe Gen4 x16 FHFL expansion slots
- 2 x PCIe Gen4 x16 HHHL expansion slots
- 1 x OCP 3.0 Gen4 x16 mezzanine slot
- 800W 80 PLUS Platinum single power supply

Specification

Dimensions	1U W435 x H43.8 x D400 mm	Backplane I/O	2 x 2.5" SATA/SAS/Gen4 NVMe ports Speed and bandwidth: SATA 6Gb/s, SAS 12Gb/s or PCIe Gen4 x4 per port
Motherboard	MZE2-G10	TPM	1 x TPM header with SPI interface Optional TPM2.0 kit: CTM010
CPU	AMD EPYC™ 7003 Series processors Single processor, 7nm technology, cTDP up to 240W Up to 64-core, 128 threads per processor TDP up to 225W, cTDP up to 240W Compatible with AMD EPYC™ 7002 Series processors	Power Supply	Single 800W 80 PLUS Platinum power supply
Chipset	System on Chip	System Management	Aspeed® AST2600 management controller GIGABYTE Management Console (AMI MegaRAC SP-X)
Memory	8-Channel DDR4 memory, total 8 x DIMM slots RDIMM/LRDIMM modules up to 128GB supported Memory speed: Up to 3200 MHz	OS Compatibility	Windows Server 2016 / 2019 RHEL 8.3 (x64) or later SLES 12 SP5 (x64) / 15 SP2 (x64) or later Ubuntu 18.04.5 LTS (x64) / 20.04 LTS (x64) or later VMware ESXi 6.7 Update3 P03 / 7.0 Update1 or later Citrix Hypervisor 8.2.0 or later
LAN	2 x 1Gb/s LAN ports (Intel® I350-AM2) 1 x 10/100/1000 management LAN	Weight	-
Video	Integrated in Aspeed® AST2600 2D Video Graphic Adapter with PCIe bus interface 1920x1200@60Hz 32bpp, DDR4 SDRAM	System Fans	2 x 40x40x28mm (25,000rpm) 5 x 40x40x56mm (25,000rpm)
Storage	2 x 2.5" SATA/SAS/Gen4 NVMe hot-swappable HDD/SSD bays SAS card is required for SAS devices support 2 x M.2 slots on CMTP182 Riser Card	Operating Properties	Operating temperature: 10°C to 35°C Operating humidity: 8-80% (non-condensing) Non-operating temperature: -40°C to 60°C Non-operating humidity: 20%-95% (non-condensing)
RAID	-	Packaging Content	1 x E152-ZE0 1 x CPU heatsinks 1 x Rail kit (optional)
Expansion Slots	2 x Full-height Full-length PCIe Gen4 expansion slots 2 x Low profile Half-length PCIe Gen4 expansion slots 1 x OCP 3.0 mezzanine slot with PCIe Gen4 x16 bandwidth Supported NCSI function	Reference Numbers	Barebone package: 6NE152ZE0MR-00 - Motherboard: 9MZE2G10NR-00 - Rail kit: 25HB2-3A0205-C0R - CPU heatsink: 25ST1-453211-A3R - Riser card - CRSE520: 9CRSE520NR-00 - M.2 Riser card: 9CMTP182NR-00 - Power supply: 25EP0-208004-L0S
Internal I/O	1 x TPM header 1 x USB 3.0 header, 1 x Front panel header, 1 x Back plane board header		
Front I/O	2 x USB 3.0, 1 x miniDP, 2 x RJ45, 1 x MLAN, 1 x Power button with LED, 1 x ID button with LED, 1 x System status LED		
Rear I/O	-		

* All specifications are subject to change without notice. Please visit our website for the latest information.

* AMD, the AMD Arrow logo, EPYC, and combinations thereof are trademarks of Advanced Micro Devices, Inc.

